



SEEDS comes in the following 2 Editions in the 2009 release: **Platinum and Silver.**

Some of our example base configuration:

	Silver	Silver	Platinum*
Users	100	300	500
Processor	Dual Core AMD Opteron [2216 2,4 GHz 2 x Socket F (1207) Hyper-Transport 1GHz]	Dual Core AMD Opteron [2216 2,4 GHz 2 x Socket F (1207) Hyper-Transport 1GHz]	Dual Core AMD Opteron [2216 2,4 GHz 2 x Socket F (1207) Hyper-Transport 1GHz]
Operating System	Windows Server® 2003 R2, Enterprise Edition, Includes 5 CALs	Windows Server® 2003 R2, Enterprise Edition, Includes 5 CALs	Windows Server® 2003 R2, Enterprise Edition, Includes 5 CALs
Additional Processor	Only one Processor	Dual Core AMD Opteron [2216 2,4 GHz 2 x Socket F (1207) Hyper-Transport 1GHz] expandable to 4 processors	Dual Core AMD Opteron [2216 2,4 GHz 2 x Socket F (1207) Hyper-Transport 1GHz] expandable to 4 processors
Memory	4 GB [DDR2 1024 Mb BUS 667 ECC REG WITH PARITY] Total Slots: 8 Expandable Up to 32GB	4 GB [DDR2 1024 Mb BUS 667 ECC REG WITH PARITY] Total Slots: 8 Expandable Up to 32GB	4 GB [DDR2 1024 Mb BUS 667 ECC REG WITH PARITY] Total Slots: 8 Expandable Up to 32GB
Hard Drive 1	160Gb Hot swappable SATA2 HITACHI 7200RPM 16 Mb CACHE	240Gb Hot swappable SATA2 HITACHI 7200RPM 16 Mb CACHE	320Gb Hot swappable SATA2 HITACHI 7200RPM 16 Mb CACHE
Hard Drive 2	160Gb Hot swappable SATA2 HITACHI 7200RPM 16 Mb CACHE	240Gb Hot swappable SATA2 HITACHI 7200RPM 16 Mb CACHE	320Gb Hot swappable SATA2 HITACHI 7200RPM 16 Mb CACHE

Hard Drive 3	160Gb Hot swappable SATA2 HITACHI 7200RPM 16 Mb CACHE	240Gb Hot swappable SATA2 HITACHI 7200RPM 16 Mb CACHE	320Gb Hot swappable SATA2 HITACHI 7200RPM 16 Mb CACHE
Hard Drive 4	160Gb Hot swappable SATA2 HITACHI 7200RPM 16 Mb CACHE	240Gb Hot swappable SATA2 HITACHI 7200RPM 16 Mb CACHE	320Gb Hot swappable SATA2 HITACHI 7200RPM 16 Mb CACHE
Storage	SAS Controller: LSI 1068 PCI-X 8 ports SAS controller: RAID 1		
Network Adaptor	2 x Gigabit Network cards [BROADCOM BCM5721 GIGABIT LAN]		
DVD / CD	Slim Type DVD-RW		
Chassis Configuration	1 x ASUS rack mount SERVER MODEL RS163E4RX4 OPTERON SAS		
Support	24 / 7 Archway Hotline Support including help desk, trouble ticket and knowledge base		
Power Supply	1 x 700 W power supplies	2 power supplies [700W 1+1 Hot-Swap Redundant Power Supply]	2 power supplies [700W 1+1 Hot-Swap Redundant Power Supply]
Graphics	1 x Video Card [VGA: ATI ES1000 VGA Controller / 32MB DDR SDRAM]		
Onboard IO	1 x External Serial Port, 3 x RJ-45 ports (1x RJ-45 optional for iKVM), 4 x USB 2.0 ports (Front x 2, Rear x 2), 1 x VGA port, 1 x PS/2 keyboard port, 1 x PS/2 mouse port		
Dimensions	Dimensions: 686mm x 444mm x 43.4mm, Approximate weight: 17kg		
Safety	Europe (TUV / CE, EN55022 compliance to EU Directive 89 / 366/ EEC)		
Environment	Operation temperature: 10°C ~ 35°C, Non operation temperature: -40°C ~ 70°C, Non operation humidity: 20% ~ 90% (Non condensing)		

*Platinum Edition comes with a second (SSX) Machine which has the same specification as the Silver.

